


ICC Cable

ICC Cable 2 m · 3m · 5 m · 10 m · 20 m



ws	wit	blanc	weiss	white
br	bruin	brun	braun	brown
gn	groen	vert	grun	green
ge	geel	jaune	gelb	Yellow
gr	grijs	gris	grau	grey
rs	roos	rose	rosa	pink
bl	blauw	bleu	blau	blue
rt	rood	rouge	rot	red
sw	zwart	noir	schwarz	black
vi	paars	violet	violett	violet
be	beige	beige	beige	tan
or	oranje	orange	orange	orange

TOP VIEW CONNECTOR:



pair	color code	T568B	PIN	T568B
1	ws-bl	5	1	ws-or
	bl	4	2	or
2	ws-or	1	3	ws-gn
	or	2	4	bl
3	ws-gn	3	5	ws-bl
	gn	6	6	gn
4	ws-br	7	7	ws-br
	br	8	8	br

Terminal no. 1 is the one on the far left as you face the cable opening, latch tab down.

Specifications

General

Conductor size	24 AWG (7 × 0.20 mm + 0.005 mm) stranded copper wire
Dielectric diameter	0.95 + 0.03mm
Number of twist pairs	4
Plug	Modular U.S. shielded type 10P10C
Jacket Material	LSZH

Product Numbers

71.60.4002	2 meters
71.60.4002	3 meters
71.60.4005	5 meters
71.60.4010	10 meters
71.60.4020	20 meters

