

AUDAC

► Features

- Design ceiling loudspeakers in modern metal housing, with an aluminium grill
- True-to-nature sound reproduction
- Quick and easy installation
- Discreet mount in wall or ceiling
- Wide dispersion sound
- High efficiency
- Shielded neodymium magnet
- Built-in self resetting protection circuit

► Applications

- Offices
- Boutiques
- Shops
- Hotel rooms
- Private houses



The CS3.2 Cuban speaker features a 1" soft dome tweeter and a 3 1/8 " full range loudspeaker with shielded neodymium magnets, which are capable of producing up to 20 W RMS with a maximum of 40 W.

The uniquely designed CUBAN square loudspeakers are flush-mounted ceiling and/or wall speakers, which provide high-quality, wide-dispersion sound while remaining as discreet as possible. Efficiency is very important for inside-wall applications.

AUDAC's highly efficient Cuban series answers to this need with its ability to generate great sound with very little power. In fact, the Cuban speaker can generate sound from solid surfaces by utilizing only 3 to 25 watts.

These high-performance speakers have a small-perforated designer grill and are ideal for offices, boutiques, shops and hotel rooms. If used in combination with an AUDAC subwoofer, the sound will be even better. A built-in self resetting protection circuit guarantees a long lifetime without any loss of quality or power.

The Cuban speakers are made of a strong, metal housing with easy mounting springs for quick and comfortable installation.

The front shows a black aluminum grid embedded in an aluminum frame, giving the speaker a dazzlingly modern design. When an additional line transformer, like AUDAC's CTR06 or CTR24, is applied, the Cuban series speaker can be perfectly adapted in a 100V speaker line application.

► Specifications

SYSTEM SPECIFICATIONS	
Max. power	40 W
RMS power	20 W
Frequency response -3dB	180 Hz - 20 kHz
Sound pressure 1 W / 1m	86 dB
Sound pressure max W / 1m	102 dB
Impedance	8 Ohm
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	193 x 122 x 106 mm
Weight net	1.28 Kg
Drivers	1" Soft dome tweeter + 3 1/8" woofer
Construction	Metal housing
Connection cable length	400 mm
Mounting	Mounting springs
Front finish	Brushed aluminium frame with Black aluminium grill
Colour	Brushed aluminium + Black
Cut-out measurement	175 x 105 mm
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	1.28 Kg - 0.07 Cbm
Accessories	CTR06: 100 V Line transformer 6 W CTR24: 100 V Line transformer 24 W
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	