

# FCS 6321

## Flush-Mounted Chairman Unit



- **Stylish Aluminum Extrusion**
- **Advanced Cat5e Cabling for Digital Series- parallel daisy-chain connection.**
- Chairman unit can be linked anywhere withing the chain (Max 10 Chairman unit)
- Chairman features priority speak button to override delegate
- Features electrets condenser stem microphone
- "Talk" button to activate/deactivate microphone
- Stereo earphone jack\*1; Rec\*1
- BXB gooseneck microphones adopt DIN type plug preventing bad contact of the connector
- Pluggable gooseneck microphone
- Illuminated red light ring for easy identification of speaker
- Quick access to "Chairman" mode
- Automatic test function
- Stem length: 43/48/56/70 cm (17", 18.9", 22", 27.6")
- MIC Auto-Off: 10-99 seconds
- With a built-in DSP chip, adjusting the audio output and sensitivity automatically

### Information

BXB ELECTRONICS CO., LTD

TEL : +886(7)970-3838

FAX : +886(7) 970-3883

Email: [bxm@bxm.tw](mailto:bxm@bxm.tw)

<http://www.bxm.tw>

6F-1, No.288-5, Shin Ya Road,  
Chien Chen District,  
Kaohsiung, Taiwan, R.O.C.  
80673



### TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
Sensitivity	≥ -50dB
Total Harmonic distortion	≤ 0.1%
S/N ratio	≥ 70dB
Voltage	DC 12V~18V
Connections	RJ-45 Jack x 2 (2.5M/20M Cat 5e)
Auto Gain Control (AGC)	-45 ~ 0dB
Earphone jack	3.5Ø Stereo
REC jack	3.5Ø Stereo
Height x Width x Depth	75x 170 x 43 ( mm )
Weight	346g w/o microphone
Material	Galvanized sheet steel
Surface	Aluminum extrusion