

► Features

- Passive crossover filter
- Integrated 35 mm pole flange adapter
- Two integrated carry handles for easy transportation
- Flat frequency response
- Dual coil 12" driver
- Scratch-free textured EPDM coating

► Applications

- High power indoor applications
- Clubs
- Theatre
- Broadcast
- PA systems



The AUDAC SX12 is a compact, light-weight dual 12" subwoofer-cabinet.

This subwoofer is perfect for any small indoor application.

The use of a passive crossover filter makes it possible that a small PA-set can be driven by only one amplifier!

An ideal solution for upgrading your PX108 or PX110 set.

The cabinet is constructed of 18 mm multi-ply hardwood and coated with scratch free and durable black textured EPDM coating.

Its built-in 35 mm pole flange adapter on top of the unit makes it possible to combine with any top-cabinet of your choice.

The stereo input is one 4-pole speakon connector combined with 2 additional output connectors for mid - high drivers.

All speakon connectors are Neutrik NL4MP to ensure that the best possible connections are made.

On both sides of the speaker are carry handles provided, to facilitate the transportation.

► Specifications

| SYSTEM SPECIFICATIONS | |
|---|--|
| Max power | 2 x 200 W |
| RMS power | 2 x 100 W |
| Impedance speaker | 2 x 8 Ohm |
| Sound pressure 1W/1m | 95 dB |
| Sound pressure Max W/1m | 118 dB |
| Frequency response -3dB | 45 Hz - 250 Hz |
| Frequency range -10dB | 42 Hz - 250 Hz |
| Cross-over frequency | 150 Hz |
| Crossover network | Passive built-in |
| PRODUCT FEATURES | |
| Dimensions (Width x Height x Depth) | 420 x 600 x 540 mm |
| Weight net | 32 Kg |
| Drivers | 2 x 12" Woofer |
| Connectors | 3 x Speakon NL4MP Neutrik (1 in / 2 out) |
| Construction | Plywood with textured EPDM black coating |
| Front finish | Open |
| Carry handles | 2 Integrated in the cabinet |
| Stand fitting | 35 mm pole adapter on top of cabinet |
| Colour | Black |
| SHIPPING & ORDERING | |
| Packaging | Carton box |
| Shipping weight & volume | 35 Kg - 0.2 Cbm |
| *AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products | |